I²C Output to Next Device

| GND | +5V | SDA | SCL |

Linx LICAL MS Series Key Fob Decoder

418 MHz Key Fob Receiver

Valid LED Illuminates when Remote Key Fob Button is Pressed

Key Fob Button LEDs Illuminate when Corresponding Key Fob Buttons are Pressed

5V I²C Level Shifter

Power LED

Key Fob Pairing Button

Key Fob Pairing Button

Raspberry Pi2 Pass-Through Connector

RP-SMA Key Fob Receiver Antenna Connector

LINX Lical Key Fob Decoder: (MS Series Key Fob)
Key Fob Button 0 is Connected to Raspberry Pi2 Pin 29 - GPIO5
Key Fob Button 1 is Connected to Raspberry Pi2 Pin 31 - GPIO6
Key Fob Button 2 is Connected to Raspberry Pi2 Pin 33 - GPIO13
Key Fob Button 3 is Connected to Raspberry Pi2 Pin 35 - GPIO19
Key Fob Button 4 is Connected to Raspberry Pi2 Pin 37 - GPIO26
Key Fob Button 5 is Connected to Raspberry Pi2 Pin 40 - GPIO21
Key Fob Button 6 is Connected to Raspberry Pi2 Pin 38 - DPIO20
Key Fob Button 7 is Connected to Raspberry Pi2 Pin 36 - GPIO16

CE
CONTROLEVERYTHING.COM